



The Detroit Speed, Inc. fuel pump connection harness was designed to be used with the DSE SuperTank 600 Series narrowed stainless steel fuel tank. This harness will give you a simple and clean connection to properly bring power to your in-tank fuel pump. This item is included with all DSE SuperTank 600 Series Fuel Tanks.

### Connecting the Fuel Pump Connection Harness to your vehicle:

1. Remove the Connector Position Assurance (CPA) Lock from the pump connector by depressing the gray tab down and pulling the CPA Lock out of the pump connector.
2. Plug the main pump connector into the fuel pump.
3. Reinstall the Connector Position Assurance (CPA) Lock into the pump connector to secure the connection.
4. Connect the 14 gauge gray wire to a 20 amp minimum, 12 volt fused ignition circuit. Use the ECM fuel pump control circuit (fuel pump trigger wire).
5. Connect the 14 gauge black wire to a good chassis ground.
6. If you have any questions, before, during, or after the installation of this product, please contact Detroit Speed , Inc. at [info@detroitsspeed.com](mailto:info@detroitsspeed.com), or by phone at 704-662-3272



[www.detroitsspeed.com](http://www.detroitsspeed.com) 704-662-3272

Detroit Speed, Inc.

SuperTank 600 Series  
Jumper Harness

P/N 080204 (510300)

92969961 instruction rev 1.0 8/25/2015